

COO-VAR®

PAINTS, PRIMERS AND SPECIALISED COATINGS

SAFETY DATA SHEET

131/W221 - PROFLOOR HIGH PERFORMANCE WB PRIMER - HARDENER

According to Regulation (EC) No 1907/2006, Annex II, as amended. Commission Regulation (EU) No 2015/830 of 28 May 2015.

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name 131/W221 - PROFLOOR HIGH PERFORMANCE WB PRIMER - HARDENER

Product number 131/W221/1 - HARDENER

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses HARDENER FOR TWO COMPONENT PRIMER

1.3. Details of the supplier of the safety data sheet

Supplier COO-VAR
Lockwood Street
Hull
HU2 0HN
+44 (0) 1482 328053(T)
+44 (0) 1482 219266(F)
info@coo-var.co.uk

Contact person Technical Department -, 08.30 - 16.30 hrs Mon - Thurs, 08.30 - 15.00 hrs Fri, as above

1.4. Emergency telephone number

Emergency telephone +44 (0) 1482 328053 Coo-Var (08.30 - 16.30 hrs Mon - Thurs, 08.30 - 15.00 hrs Fri)

SDS No. 10807

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (EC 1272/2008)

Physical hazards Not Classified

Health hazards Eye Dam. 1 - H318

Environmental hazards Not Classified

Human health May cause skin sensitisation or allergic reactions in sensitive individuals.

2.2. Label elements

Pictogram



Signal word Danger

Hazard statements H318 Causes serious eye damage.

131/W221 - PROFLOOR HIGH PERFORMANCE WB PRIMER - HARDENER

Precautionary statements	P102 Keep out of reach of children.
	P101 If medical advice is needed, have product container or label at hand.
	P262 Do not get in eyes, on skin, or on clothing.
	P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.
	P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.
	P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
	P313 Get medical advice/ attention.
	P403+P233 Store in a well-ventilated place. Keep container tightly closed.
	P501 Dispose of contents/ container in accordance with national regulations.

Contains	Teta, polymer with Bisphenol A diglycidyl Ether, Formaldehyde, MXDA, sulphamic acid and Ethoxylated nonyl Phenol
-----------------	--

2.3. Other hazards

This product does not contain any substances classified as PBT or vPvB.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Teta, polymer with Bisphenol A diglycidyl Ether, Formaldehyde, MXDA, sulphamic acid and Ethoxylated nonyl Phenol		10-30%
CAS number: 238080-05-2		
Classification	Classification (67/548/EEC or 1999/45/EC)	
Acute Tox. 4 - H302 Eye Dam. 1 - H318	Xn;R22. Xi;R41.	
Barium Sulphate		10-30%
CAS number: 7727-43-7	EC number: 231-784-4	REACH registration number: 01-2119491274-35-0001
Classification	Classification (67/548/EEC or 1999/45/EC)	
Not Classified	-	
Calcium Magnesium Silicate		10-30%
CAS number: 14807-96-6	EC number: 238-877-9	
Classification	Classification (67/548/EEC or 1999/45/EC)	
Not Classified	-	
Silicon dioxide, chemically prepared		<1%
CAS number: 7631-86-9	EC number: 231-545-4	REACH registration number: 01-2119379499-16-0000
Classification		
Not Classified		

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

131/W221 - PROFLOOR HIGH PERFORMANCE WB PRIMER - HARDENER

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation	Remove affected person from source of contamination. Get medical attention if any discomfort continues.
Ingestion	Rinse mouth thoroughly with water. Do not induce vomiting. If vomiting occurs, the head should be kept low so that stomach vomit doesn't enter the lungs. Give plenty of water to drink. Get medical attention immediately.
Skin contact	Remove contaminated clothing immediately and wash skin with soap and water. Get medical attention if any discomfort continues.
Eye contact	Remove any contact lenses and open eyelids wide apart. Rinse immediately with plenty of water. Continue to rinse for at least 15 minutes. Get medical attention immediately. Continue to rinse.

4.2. Most important symptoms and effects, both acute and delayed

Ingestion	Harmful if swallowed.
Eye contact	Causes serious eye damage. May cause permanent damage if eye is not immediately irrigated.

4.3. Indication of any immediate medical attention and special treatment needed

Notes for the doctor	Treat symptomatically.
-----------------------------	------------------------

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	Extinguish with alcohol-resistant foam, carbon dioxide, dry powder or water fog.
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.

5.2. Special hazards arising from the substance or mixture

Hazardous combustion products	Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapours.
--------------------------------------	--

5.3. Advice for firefighters

Special protective equipment for firefighters	Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing.
--	---

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions	Follow precautions for safe handling described in this safety data sheet. Avoid inhalation of vapours and contact with skin and eyes. Provide adequate ventilation.
-----------------------------	---

6.2. Environmental precautions

Environmental precautions	Avoid discharge into drains or watercourses or onto the ground. Spillages or uncontrolled discharges into watercourses must be reported immediately to the Environmental Agency or other appropriate regulatory body.
----------------------------------	---

6.3. Methods and material for containment and cleaning up

Methods for cleaning up	Absorb with inert, damp, non-combustible material, then flush area with water. Collect and place in suitable waste disposal containers and seal securely. For waste disposal, see Section 13.
--------------------------------	---

131/W221 - PROFLOOR HIGH PERFORMANCE WB PRIMER - HARDENER

6.4. Reference to other sections

Reference to other sections For personal protection, see Section 8. For waste disposal, see Section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Usage precautions Avoid inhalation of vapours/spray and contact with skin and eyes. Provide adequate ventilation.

7.2. Conditions for safe storage, including any incompatibilities

Storage precautions Store in tightly-closed, original container in a dry, cool and well-ventilated place.

Storage class Miscellaneous hazardous material storage.

7.3. Specific end use(s)

Specific end use(s) The identified uses for this product are detailed in Section 1.2.

SECTION 8: Exposure controls/Personal protection

8.1. Control parameters

Occupational exposure limits

Barium Sulphate

Long-term exposure limit (8-hour TWA): 10 mg/m³ inhalable dust

Long-term exposure limit (8-hour TWA): 4 mg/m³ respirable dust

Calcium Magnesium Silicate

Long-term exposure limit (8-hour TWA): WEL 1 mg/m³

Silicon dioxide, chemically prepared

Long-term exposure limit (8-hour TWA): WEL 2.4 mg/m³ respirable dust

Long-term exposure limit (8-hour TWA): WEL 6 mg/m³ inhalable dust

WEL = Workplace Exposure Limit

8.2. Exposure controls

Protective equipment



Appropriate engineering controls

Provide adequate ventilation. Mechanical ventilation or local exhaust ventilation may be required. Ensure operatives are trained to minimise exposure.

Personal protection

Unprotected persons should be kept away from treated areas.

Eye/face protection

The following protection should be worn: Wear eye protection. Tight-fitting safety glasses. Full face visor or shield. Workers should not contact their eyes or skin with hands contaminated with the material.

131/W221 - PROFLOOR HIGH PERFORMANCE WB PRIMER - HARDENER

Hand protection	To protect hands from chemicals, gloves should comply with European Standards EN388 and 374. As a general principle, exposure should be managed by means other than the provision of protective gloves. Manufacturer's performance data suggest that the optimum glove for use should be: Nitrile rubber. Thickness: ≥ 0.3 mm Neoprene. Thickness: ≥ 0.4 mm or Butyl rubber. Thickness: ≥ 0.3 mm Permeation breakthrough time according to EN374 - class: (1-6) e.g. minimum 480 mins. Caution: The performance of gloves under actual working conditions can be significantly affected by many factors and the information provided according to EN374 may not accord with what is achieved in practice. We recommend that expert professional advice is sought that takes into account of the work processes and working environment applicable for each task where gloves are to be worn.
Other skin and body protection	Wear suitable protective clothing as protection against splashing or contamination.
Hygiene measures	Wash at the end of each work shift and before eating, smoking and using the toilet.
Respiratory protection	If ventilation is inadequate, suitable respiratory protection must be worn. Full face mask respirators with replaceable filter cartridges should comply with European Standard EN136. Half mask and quarter mask respirators with replaceable filter cartridges should comply with European Standard EN140.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance	Viscous liquid. Liquid
Colour	White / off-white.
Odour	Ammonia.
Odour threshold	Not determined.
pH	pH (concentrated solution): 8.9
Initial boiling point and range	$>100^{\circ}\text{C}$ @ 760 mm Hg
Flash point	above 100°C Closed cup.
Evaporation rate	Not determined.
Evaporation factor	Not determined.
Flammability (solid, gas)	Not applicable.
Upper/lower flammability or explosive limits	Data lacking.
Vapour pressure	15 mm Hg @ $^{\circ}\text{C}$
Vapour density	Not determined.
Relative density	1.30 @ @ 20°C
Solubility(ies)	Soluble in water.
Auto-ignition temperature	150°C
Decomposition Temperature	Not determined.
Explosive properties	Not applicable.
Oxidising properties	Data lacking.

9.2. Other information

Other information	No information required.
--------------------------	--------------------------

131/W221 - PROFLOOR HIGH PERFORMANCE WB PRIMER - HARDENER

Volatile organic compound This product contains a maximum VOC content of 0 g/litre.

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity No test data specifically related to reactivity available for this product or its ingredients.

10.2. Chemical stability

Stability Stable at normal ambient temperatures and when used as recommended.

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions The following materials may react violently with the product: Peroxides.

10.4. Conditions to avoid

Conditions to avoid Avoid excessive heat for prolonged periods of time.

10.5. Incompatible materials

Materials to avoid Acids. sodium hypochlorite Peroxides.

10.6. Hazardous decomposition products

Hazardous decomposition products Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapours.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity - oral

ATE oral (mg/kg) 2,876.16

Skin corrosion/irritation

Animal data Data lacking.

Serious eye damage/irritation

Serious eye damage/irritation Causes serious eye damage.

Respiratory sensitisation

Respiratory sensitisation Data lacking.

Skin sensitisation

Skin sensitisation Data lacking.

Germ cell mutagenicity

Genotoxicity - in vitro Data lacking.

Carcinogenicity

Carcinogenicity Data lacking.

Reproductive toxicity

Reproductive toxicity - fertility Data lacking.

Specific target organ toxicity - single exposure

STOT - single exposure Data lacking.

Specific target organ toxicity - repeated exposure

STOT - repeated exposure Data lacking.

Aspiration hazard

131/W221 - PROFLOOR HIGH PERFORMANCE WB PRIMER - HARDENER

Aspiration hazard	Based on available data the classification criteria are not met.
Inhalation	Gas or vapour in high concentrations may irritate the respiratory system.
Ingestion	Harmful if swallowed.
Skin contact	May cause sensitisation or allergic reactions in sensitive individuals. Prolonged skin contact may cause temporary irritation.
Eye contact	Causes serious eye damage.

Toxicological information on ingredients.

Barium Sulphate

Acute toxicity - oral

Acute toxicity oral (LD₅₀ mg/kg) 15,000.0

Species Rat

ATE oral (mg/kg) 15,000.0

SECTION 12: Ecological information

Ecotoxicity The product components are not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.

12.1. Toxicity

Acute aquatic toxicity

Acute toxicity - fish No information available.

12.2. Persistence and degradability

Persistence and degradability There are no data on the degradability of this product.

12.3. Bioaccumulative potential

Bioaccumulative potential No data available on bioaccumulation.

12.4. Mobility in soil

12.5. Results of PBT and vPvB assessment

Results of PBT and vPvB assessment This product does not contain any substances classified as PBT or vPvB.

12.6. Other adverse effects

Other adverse effects Not determined.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

General information Waste is classified as hazardous waste. Do not puncture or incinerate even when empty.

Disposal methods Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority.

131/W221 - PROFLOOR HIGH PERFORMANCE WB PRIMER - HARDENER

Waste class Used containers, drained and/or rigorously scraped out and containing dry residues of the supplied coating, are categorised as non-hazardous waste, with code 15 01 02 (plastic packaging) or 15 01 04 (metal packaging). Wear protective clothing during disposal operations. If disposal is by waste contractor, make sure that he has sufficient information and that waste containers are properly labelled. Ideally this component should be mixed with the appropriate resin base and allowed to react fully producing a solid non hazardous waste.

SECTION 14: Transport information

General The product is not covered by international regulations on the transport of dangerous goods (IMDG, IATA, ADR/RID).

14.1. UN number

Not applicable.

14.2. UN proper shipping name

14.3. Transport hazard class(es)

No transport warning sign required.

14.4. Packing group

Not applicable.

14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant

No.

14.6. Special precautions for user

Not applicable.

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not applicable.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU legislation

Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) (as amended).
Commission Regulation (EU) No 2015/830 of 28 May 2015.
Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures (as amended).

15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

SECTION 16: Other information

Revision comments

Issued in new format for Reach compliance in accordance with EC 1272/2008 Issued in accordance with Annex II to REACH, as amended by Commission Regulation (EU) No. 2015/830 Amendment to Section 8.2, recommendations for respiratory protective equipment and hand protection. Revisions to Sections (2),(3),(8),(15), and (16) - re-classification of resin components.

131/W221 - PROFLOOR HIGH PERFORMANCE WB PRIMER - HARDENER

Issued by	Technical Dept. (P.E.)
Revision date	08/11/2018
Revision	7.0
Supersedes date	23/01/2016
SDS number	10807
SDS status	Approved.
Hazard statements in full	H302 Harmful if swallowed. H318 Causes serious eye damage.
Signature	Initials

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.