

HAMMERCOTE THINNERS

600/V607/15

DESCRIPTION:

Hammercote Thinners is a C8 - C10 Aromatic hydrocarbon solvent mixture.

RECOMMENDED USE:

As a slow evaporating thinner / brushwash for Coo-Var Hammercote. See specified thinners for paint being used.

AVAILABILITY:

0.25 litre, 0.5 litre, 1 litre, 2.5 litre

FINISH:

N/A

COLOUR:

Clear thin liquid.

TYPICAL S.G. (SPECIFIC GRAVITY):

0.86 @ 20 °C

VOLUME SOLIDS:

N/A

WET FILM THICKNESS W.F.T

N/A

DRY FILM THICKNESS D.F.T

N/A

EXPECTED SPREADING RATE:

N/A

The practical spreading rate may be lower as this depends on factors such as the porosity and roughness of the surface to be painted and material losses during application.

TYPICAL VISCOSITY

N/A

FLASH POINT:

41 °C (closed cup)

DRYING TIME: @ RECOMMENDED D.F.T

Touch dry: N/A

Hard dry: N/A

Full hardness: N/A

Low temperature and high humidity will adversely affect application, drying and performance of any coating.

MINIMUM OVERCOATING TIME:

N/A

APPLICATION SPECIAL CONDITIONS:

N/A

VOC CONTENT:

N/A

VOC's (Volatile Organic Compounds) contribute to atmospheric pollution

APPLICATION DETAILS:

Application restrictions N/A

Method N/A

Thinner (Max vol): N/A

Nozzle size: N/A

Nozzle pressure: N/A

Cleaning solvent: N/A

Recoat interval: N/A

SURFACE PREPARATION:

N/A

MIXING INSTRUCTIONS:

N/A

APPLICATION CONDITIONS:

N/A

For further advice contact Coo-Var Technical Services on +44(0)1482 328053

The physical constants are subject to normal manufacturing tolerances.

"COVERING OUR CUSTOMERS' NEEDS SINCE 1908"

Ellenshaw Works

Lockwood Street, Hull HU2 0HN

Tel.: +44(0)1482 328053. Fax: +44(0)1482 219266

COO-VAR

Email: info@coo-var.co.uk

www.coo-var.co.uk

HAMMERCOTE THINNERS**600/V607/15**

PRECEDING COAT:

N/A

SUBSEQUENT COAT:

N/A

REMARKS:

Flamability limits in air:- Lower - 0.6% by volume
Upper - 7% by volume

Vapour pressure:- 2.9mm HG @ 20°C

HEALTH AND SAFETY:

See safety data sheet - SDS 10703

ISSUED:

17 September 2009

REVISION:

0

The information given in this data sheet is based on experience and is accurate to the best of our knowledge. No guarantee should be implied, however, since the conditions of use are beyond our control. This data sheet does not constitute a specification. In case of doubt as to the suitability of the product please contact our Technical Service Department on 01482 328053.

For further advice contact Coo-Var Technical Services on +44(0)1482 328053

The physical constants are subject to normal manufacturing tolerances.

"COVERING OUR CUSTOMERS' NEEDS SINCE 1908"

Ellenshaw Works

Lockwood Street, Hull HU2 0HN

Tel.: +44(0)1482 328053. Fax: +44(0)1482 219266

COO-var

Email: info@coo-var.co.ukwww.coo-var.co.uk