

TECHNICAL HEALTH AND DATA SHEET

PRODUCT:- ACRYLIC FLOOR PAINT
CLEAR GLAZE

REFERENCE:- W/138/T

COLOUR:- CLEAR

FINISH:- SEMI-GLOSS

TYPE:- AQUEOUS COPOLYMER

TYPICAL SG:- 1.03 AT 20°C

TYPICAL VISCOSITY:- 2.5 POISE AT 25°C

TYPICAL TOTAL SOLIDS:- 41.5% BY WEIGHT

FLASH POINT:- NON-FLAMMABLE

RECOMMENDED THINNERS:- CLEAN WATER

APPLICATION:- BRUSH OR ROLLER

*COVERAGE GUIDE:- 11 SQ. METRES/LITRE

*DRYING TIME:- SURFACE DRY - 1½ HOURS
THROUGH DRY - 6 HOURS
COLD, DAMP CONDITIONS WILL
PROLONG THESE TIMES.

STORAGE:- PROTECT FROM FROST AND
ABNORMAL HEAT

USES:- AS A CLEAR WATER BASED FLOOR
PAINT.FOR WOODEN FLOORS

HEALTH & SAFETY:- SEE SHEET HSD 'B'

*BY BRUSH TO A DRIED FILM THICKNESS OF 20-25 MICRONS AT 20°C.

COO-VAR

PAINTS, PRIMERS & SPECIALISED COATINGS

Ellenshaw Works, Lockwood Street, HULL. HU2 OHN
Telephone : 01482-328053 Fax: 01482-219266