

F138

FLEETWOOD CEILING PAINT

CHARACTERISTICS

Ceiling paint is a premium quality, high hiding, easy to apply, drip resistant finish for new and old ceilings. Beautiful non-yellowing ceiling flat white. Low odour. Free from lead hazards - safe for children's rooms. Durable - Economic. One coat. Drip resistant.

DRYING SCHEDULE

Dry to recoat:- 2-3 hours (under normal ventilated conditions).

WEIGHT SOLIDS

45.0+/-2%

VOLUME SOLIDS

30.0+/-1%

PRECAUTIONS

Keep out of reach of children.

Ensure good ventilation during application and drying.

In case of contact with eyes rinse immediately with plenty of water.

Remove splashes from skin using soap and water or a recognised skin cleaner.

Protect from freezing.

APPLICATION
The product is supplied ready for use.

SPREADING RATE

5 US gal cover approx. 230m² over smooth non-porous surface.

METHODS

Brush, roller or paint pad - fast dry.

Apply generously. Avoid over-brushing

CLEAN UP

Clean up with soap and water.

REDUCTION

Can be reduced with 5% - 10% water if necessary.

SURFACE PREPARATION
Surfaces to be painted must be dry, sound and free from dirt, grease or powder. Particular care must be given to old ceilings. All flaking ceilings must be thoroughly scraped and sealed before application. Any powdery material present must be completely removed by washing or made sound by application of Stabilising Solution.