

# F79

# METAL SHIELD

## CHARACTERISTICS

Metal Shield is a quick drying acrylic modified alkyd paint designed for application to marginally prepared steel surfaces.

This self-priming product provides a tough weather resistant film with excellent adhesive properties on tightly adherent rust surfaces or previously painted surfaces with tightly adherent films. May be used as the sole protective product or as a primer under high performance alkyd enamel topcoats.

## USES

Primer/Topcoat for ferrous substrates.

Primer over rusted/pitted steel where blasting is not possible.

General purpose product for domestic metal gutters, drain pipes, gates etc.

## COLOUR

White, Silver Grey, Black, Garden Green

## SPECIFIC GRAVITY

1.29+/-0.01

## WEIGHT SOLIDS

61+/-2%

## VOLUME SOLIDS

47+/-2%

## PRECAUTIONS

Keep out of reach of children.

Ensure good ventilation during application and drying.

In case of contact with eyes rinse immediately with plenty of water.

To remove splashes from skin use soap and water or a recognised skin cleaner. Do not take internally.

## Contains no added lead. APPLICATION

SPREADING RATE

(Calculated) 8m<sup>2</sup>/lt

(86 sq ft)/lt

## DRYING SCHEDULE

To Touch:- 4 hours

To Recoat:- Overnight

## REDUCTION

Use as supplied.

Clean equipment with White Spirits. SURFACE PREPARATION

Remove all grease, oil, dust or other contaminants by solvent cleaning. Remove all loose rust using a wire brush or powered hand tool.

**Note:- Metal Shield may be applied over tight, granular rust. Do not apply over heavy rust scale.**

## PREVIOUSLY PAINTED SURFACES

Check compatibility by applying Metal Shield on a test area and inspecting for adhesion, lifting, wrinkling or other signs of incompatibility