

F117 WEATHERGUARD PLIOLITE RESIN BASED MASONRY PAINT

CHARACTERISTICS

A smooth matt masonry paint of superior quality. Specially formulated to provide maximum resistance to the elements: wind-driven rain, sun, temperature extremes and atmospheric pollution whilst at the same time retaining its decorative appearance.

MAIN PROPERTIES

Excellent adhesion to properly prepared surfaces
Alkali resistance
Breathable film
Self cleaning
Resistance to mould growth
Lasting protection

COLOUR

Brilliant White

DRYING SCHEDULE

Rain resistant approx. 20mins
To touch: 1 - 2 hours
Overcoat after overnight drying

SPECIFIC GRAVITY

1.54+/-0.02

WEIGHT SOLIDS

70+/-2%

VOLUME SOLIDS

42+/-2%

VEHICLE TYPE

Synthetic Pliolite Resin

APPLICATION

Apply liberally and evenly with brush, roller or airless spray.

For spray application thin as necessary with white spirits.

On very porous or absorbent surfaces thin first coat of Weatherguard with up to 15% by volume of White Spirit.

CONVENTIONAL AIR SPRAYING

Thin with 5-15% White Spirits as required.
Tip size: 2.0mm
Tip Pressure: 60psi (0.4MPa) approximately

AIRLESS SPRAYING

Thin with 0-10% White Spirits as required.
Tip size: 19 thou (0.48mm) approximately
Tip Pressure: 2100 psi (15MPa) approximately

SPREADING RATE

Up to 6.5 square metres per litre on smooth non porous surfaces.

PERFORMANCE INFORMATION

The product is specially designed as an exterior coating for use over block, concrete and other masonry surfaces where a long lasting decorative finish is required.

CLEAN UP

Clean equipment immediately after use with white spirits.

SURFACE PREPARATION

Surfaces to be painted must be in sound condition. Use in accordance with good painting practice. Remove oil, grease, dust and all loose or flaking paint. Remove mould, algae or other organic growth by treating with proprietary fungicidal solution.

Concrete Block and Masonry:- Surfaces should be thoroughly clean and dry, with mortar and concrete aired for a minimum of 30 days @ 24oC. All loose mortar or other contaminants should be removed prior to application of any coating material. Use appropriate filler for cracks or imperfections. Allow to dry thoroughly before top coating.

PREVIOUSLY PAINTED SURFACES

If in sound condition, clean the surface of all foreign material. Glossy surfaces must be washed and thoroughly rubbed down with waterproof abrasive paper to provide a key. If paint is peeling or badly weathered, clean to sound substrate and treat as new.

PRECAUTIONS

Flammable

Keep out of reach of children. Ensure good ventilation during application and drying.

When applying to large indoor areas or in confined spaces, wear a suitable cartridge respirator or air-fed respiratory equipment.

When spraying do not breathe spray. Wear suitable respiratory protective equipment.

In case of contact with eyes rinse immediately with plenty of water.

To remove splashes from skin use soap and water or a recognised skin cleaner. Do not take internally. Contains no added lead.