

F119

FLEETWOOD WOOD PRIMER

CHARACTERISTICS

A top quality oil based wood primer, pigmented with titanium dioxide and inert mineral extenders.

COLOUR

White

DRYING SCHEDULE

Tack Free:- 3-4 hrs under normal drying conditions.

Hard Dry:- Overnight

Overcoat:- Overnight under normal

conditions.

SPECIFIC GRAVITY

1.75+/-0.10

WEIGHT SOLIDS

81+/-2%

VOLUME SOLIDS

60+/-2%

VEHICLE TYPE

Oil modified alkyd

FLASH POINT

400C

PRECAUTIONS

Keep out of reach of children.

Ensure good ventilation during application and drying.

In case of contact with eyes rinse immediately with plenty of water.

To remove splashes from skin use soap and water or a recognised skin cleaner. Do not take internally.

Contains no added lead.

APPLICATION

PRACTICAL SPREADING RATE

(Calculated) 12-16m²

METHODS

Brush, roller, conventional airspray.

PERFORMANCE INFORMATION

This product is a premium quality base coat for bare wood that smooths and fills for a perfect paint finish when used under Fleetwood oil based paints. Suitable for softwood, plywood, chipboard etc. For highly resinous softwood use Fleetwood Aluminium Wood Primer.

CLEAN UP

Clean equipment with White Spirits.

SURFACE PREPARATION

Wood must be dry, free of dirt, grease, wax, polish and old finishes in poor condition. Sand wood to a smooth surface and remove sanding dust with a tack cloth or vacuum. Treat knots with knotting where necessary.

Stir thoroughly before use. Ideal preparation for a beautiful gloss finish when overcoated with Fleetwood

Undercoat and Gloss on properly prepared surfaces.