



Technical Product Data

a) Product Name	PLASTONE MASONRY PAINT – SMOOTH PLIOLITE
b) Reference Number	P.P.41
c) Product Description	A high quality smooth coating based on a thermoplastic resin incorporating Butadiene and Acrylic Monomers, Titanium and Iron Oxide pigments. Offers excellent colour retention. Re-inforced with Mica to give an extremely durable long term finish.
d) Uses	A smooth long life coating for Masonry Substrates
e) Pack Sizes	5 and 20 litre drums
f) Colour Range	12 colours plus white
g) Specific Gravity	1.44
h) Flash Point	35°C
i) Solids	43.7
j) Spreading Rate @ D.R.A.T	200 g / per Metre ²
k) Drying Time	Touch Dry 24 hours Full Cure 2-3 Weeks
l) Lowest Application Temperature	5°C
m) Dry Recommended Application Thickness D.R.A.T	175 Microns
n) Methods of Application	Roller & Spray Roller & Texturing, Air spray, Pressurised Pot
o) Recommended Preparation	See Preparation Sheet No 7
p) Storage Life	12 Months
q) Thinner / Cleaner	White Spirit
r) Precautions	Ensure the use of good filter masks when spraying. The use of barrier cream is recommended. Do not smoke or allow naked flames in the vicinity of work. Extreme care must be taken when spraying in enclosed area. Supply air fed masks.