

PRODUCT DATA SHEET

EVERBUILD® Wood Stain Satin

QUICK DRYING, PROFESSIONAL WOOD STAIN

PRODUCT DESCRIPTION

EVERBUILD® Wood Stain Satin is a professional, solvent free wood stain that enhances the natural qualities of wood, and provides long lasting protection. The weatherproof protection provided also gives a crack and peel resistant finish and excellent resistance to ultra violet light degradation. Under normal weathering conditions EVERBUILD® Wood Stain Satin can be expected to provide protection for up to 5 Years. Maintenance Clear Coat is also available to improve the look of Wood without altering the colour.

USES

Ideal for use on smooth planed exterior and interior timber, such as doors, window frames, architectural timbers, conservatories, cladding & garden furniture etc.

CHARACTERISTICS / ADVANTAGES

- Solvent Free formula.
- Up to 5 years protection.
- Crack and peel resistant.
- Stains and weatherproofs.
- Internal and external use.
- Touch dry in 30 minutes, overcoat after 4 hours.
- Easy to apply.
- High resistance to UV light.

PRODUCT INFORMATION

Packaging	250ml, 750ml and 2.5ltr tins
Appearance / Colour	Dark Oak, Mahogany, Natural Oak, Antique Pine, Rosewood, Teak, Walnut (available in all sizes). Maintenance Clear Coat available in 750ml and 2.5ltr size only.
Shelf Life	2 years from date of manufacture when stored as directed.
Storage Conditions	Store in cool dry conditions between + 5 and +25°C. Storage outside these conditions will dramatically reduce shelf life. PROTECT FROM FROST.
Viscosity	1500 - 2500cP @ 20°C (Brookfield RVT 4, 20 rpm)
pH-Value	Approx 7.5 - 9.0

APPLICATION INFORMATION

Consumption Coverage of up to 20 square metres per litre. Coverage will vary depending on the absorbency of the wood.

APPLICATION INSTRUCTIONS

SUBSTRATE QUALITY / PRE-TREATMENT

Ensure wood is clean, dry and free from dirt or dust. Any rough surfaces or areas should be sanded until smooth. Old varnish or paint finishes must be completely removed by sanding or stripping before applying of EVERBUILD® Wood Stain Satin. Old wood stain finishes should be cleaned and lightly sanded to provide a key before application.

MIXING

Stir product well before use and intermittently during application.

APPLICATION

Brush apply EVERBUILD® Wood Stain Satin, always following the direction of the wood grain, approximately 3 coats will be required for full benefits and performance. It is touch dry in 30 minutes, allow to dry for 4 hours in between coats, lightly sand the surface before applying the final coat taking care to only sand very lightly around edges.

Always apply the stain to a wet edge, working systematically across the surface keeping the wet edge moving together as much as possible. After applying to an area the finished appearance will be improved by feather brushing over the entire area with an unloaded brush taking care to follow the wood grain. When re-coating on darker shades of stain Maintenance Clear Coat can be used to refresh the coat without further darkening the surface (check compatibility and lightly abrade).

CLEANING OF TOOLS

Clean brushes with water after use, a little washing up liquid will assist brush cleaning.

MAINTENANCE

Inspect surfaces every 3 -5 years depending on exposure to weathering and apply top up using Everbuild Maintenance Clear coat or further Woodstain as required.

LIMITATIONS

- Colour swatch label is an indication of the colour of the stain only, **always** test the colour on an inconspicuous, small area before full scale application.
- Do not use on wood floors or decking.
- Protect from frost and do not use in temps below 10°C.
- To avoid risk of spillage, always transport this tin in a secure and upright position.
- At elevated temperatures (25°C+) or direct sun light you may not be able to maintain a wet edge and could lead to poor finish
- Ensure exterior wood/timber is treated with a non-repellent wood preservative prior to application of wood stain for complete protection. Particularly in areas subject to weathering.

- As the manufacturer cannot know all the uses its products may be put to, it is the user's responsibility to determine suitability for use. If in doubt, contact Technical Services Department for advice.

VALUE BASE

All technical data stated in this Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

LOCAL RESTRICTIONS

Note that as a result of specific local regulations the declared data and recommended uses for this product may vary from country to country. Consult the local Product Data Sheet for the exact product data and uses.

ECOLOGY, HEALTH AND SAFETY

LEGAL NOTES

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

EVERBUILD BUILDING PRODUCTS LTD

Site 41, Knowsthorpe Way
Cross Green Industrial Estate
Leeds, LS9 0SW
Tel: 0113 240 3456
Web: www.everbuild.co.uk
Twitter: @everbuild

SIKA LIMITED

Watchmead
Welwyn Garden City
Hertfordshire, AL7 1BQ
Tel: 01707 394444
Web: www.sika.co.uk
Twitter: @SikaLimited

SIKA IRELAND LIMITED

Ballymun Industrial Estate
Ballymun
Dublin 11, Ireland
Tel: +353 1 862 0709
Web: www.sika.ie
Twitter: @SikaIreland

EVERBUILDWoodStainSatin-en-GBEVER-(03-2018)-1-1.pdf

Product Data Sheet
EVERBUILD® Wood Stain Satin
March 2018, Version 01.01
020405030020000008