



# SEALANT REMOVER

## PASTE FOR REMOVING CURED SEALANT RESIDUES.



### PRODUCT DESCRIPTION

Paste for removing cured sealant residues.

### FIELD OF APPLICATION

Suitable for removing (cured) sealant residues. Suitable for ceramic tiles, glass, metal, synthetics, laminated material, aluminium and enamel.

Not suitable for nylon.

### PREPARATION

**Working Conditions:** Only apply at temperatures between +5°C and +40°C.

**Surface Requirements:** The substrate must be properly dry, clean and free of dust and grease. Remove as much of the existing sealant as possible.

**Preliminary Surface Treatment:** Use a sharp knife/putty knife to cut away the silicone sealant as much as possible and a dry cloth for the last remaining bits.

**Tools:** GRIFFON Multitool, Sharp box cutter, Cleaning Cloth, Sponge

### APPLICATION

#### Directions for use:

Shake well or stir before use.

Shake closed bottle vigorously for about a minute. Cut old sealant loose with a sharp box cutter/ knife. Use the hook of the **{Brand}** Multitool to pull out the old sealant out of the joint. Apply the paste generously onto the old sealant residue. Allow to act for at least 30 minutes. Remove old sealant residues with cleaning cloth or sponge. If necessary, repeat the treatment. Clean the joint thoroughly with a sponge and water. Degrease the surface with a lint-free cloth and ammonia. Let it dry thoroughly. Ready for a new sealant application.

**Advice:** Test the remover on a non-visible spot as staining may occur on sensitive materials.

**Points of attention:** May cause staining on porous materials and painted surfaces.

### TECHNICAL SPECIFICATIONS

Density approx.:	0,84 g/cm <sup>3</sup>
Viscosity:	Gel

### STORAGE CONDITIONS

A minimum of 24 months.

Limited shelf life after opening.

Store in properly sealed packaging in a dry place at between +5°C and +25°C.

Our advice is based on extensive research and practical experience. However, in view of the large variety of materials and the conditions under which our products are applied, we assume no responsibility for the results obtained and/or any damage caused by the use of the product. Nevertheless, our Service Department is always at your disposal for any advice needed.